



## PLICORD® DIESEL OIL SOFTWALL

### APPLICATION/SERVICE:

Heavy duty high performance discharge hose for the transfer of oil and petroleum base products including bulk supply of diesel oil from supply vessels to offshore platforms and drilling rigs.

### BENEFITS:

**TOUGH, HIGH SAFETY MARGIN** - Built to the highest standard with first class materials. The 4-ply reinforcement of high strength textile plies maintains a safety factor of 5:1 between working pressure and bursting pressure.

**LONG LIFE** - Goodyear's Chemigum® tube compound offers superb oil resistance while the Wingprene® cover withstands extremes of weather and seawater from rough seas.

### CONSTRUCTION:

Tube: Black Chemigum® synthetic rubber  
 Reinforcement: 4 ply textile plus anti static wire  
 Cover: Black Wingprene® with brown spiral stripe  
 (wrapped finish)

### BRANDING:

No branding

### LENGTHS:

18.3 mtr coils (available in other coil lengths up to max 120 mtr)

### ORDER CODES:

543272



### DIMENSIONS:

Code	ID (ins)	ID (mm)	OD (mm)	Lengths	WP (psi)	Weight (kgs/m)
20017708	3"	76.2	91.4	18.3 m	150	2.84
20017710	4"	101.6	118.1	18.3 m	150	3.72
20017710	5"	127.1	142.2	18.3m	150	4.28

(< = Stock size for UK )