



PLICORD® BARYTE HARDWALL

APPLICATION / SERVICE:

High performance suction and discharge hose for bulk transfer of barytes and non-oily abrasive materials from supply vessels to offshore platforms and drilling rigs.

BENEFITS:

EXCEPTIONAL PERFORMANCE - Built for rugged service and long life with a 4 ply reinforcement which maintains very high safety margins over the three sizes, and a tough steel wire helix for strength and stability.

SUPERIOR WEAR RESISTANCE - A thick abrasion resistant tube compound resists wearing from cement and barytes. The Plioflex® cover gives the hose excellent protection against extreme weather conditions encountered in oil rig applications.

CONSTRUCTION:

Tube: Black Tufsyn® (static conductive)

Reinforcement: 4 ply textile and helix wire

Cover: Black Plioflex® with orange spiral stripe (wrapped finish)

BRANDING:

'Goodyear™'

LENGTHS:

18.3, 30.5 mtr coils (available in other lengths up to max 120 mtr)

FITTINGS:

Long tail 'hookie-type' combination nipples screwed API

ORDER CODE:

549278



DIMENSIONS:

| Code | ID (ins) | ID (mm) | OD (mm) | Lengths | WP (psi) | Weight (kgs/m) |
|---------------------|----------|---------|---------|--------------|----------|----------------|
| 20019501 | 4" | 101.6 | 121.0 | 18.3 m | 150 | 4.59 |
| 20019502 / 20066726 | 5" | 127.0 | 150.2 | 18.3, 30.5 m | 150 | 7.90 |
| No code | 6" | 152.4 | 176.8 | 18.3 m | 150 | 9.59 |

(< = Stock size for UK)