



PLICORD® DIESEL OIL HARDWALL

APPLICATION / SERVICE:

High performance oil suction and discharge hose with brown spiral stripe. Constructed for heavy duty service in the transfer of oil and petroleum base products including diesel oil from supply vessels to offshore platforms and drilling rigs.

BENEFITS:

ROBUST, LONG LASTING - Extremely tough hardwearing hose for long service life in the most arduous working conditions. Multiple plies of tough textile reinforcement and double wire helix provide strength and unbeatable crush and kink resistance.

HIGH QUALITY COMPOUNDS - This application demands compounds of the highest standard. Goodyear's special Chemigum® tube offers maximum oil resistance and the Wingprene® cover resists the effects of extreme weather conditions.

CONSTRUCTION:

Tube: Black Chemigum® synthetic rubber

Reinforcement: 4 ply textile and 2 helix wires

Cover: Black Wingprene® with brown spiral stripe (wrapped finish)

BRANDING:

'Goodyear™'

LENGTHS:

18.3 mtr coils (available in other lengths up to max 120 mtr)

FITTINGS:

Long tail 'hookie-type' combination nipples screwed API

ORDER CODE:

543272

DIMENSIONS:



Code	ID (ins)	ID (mm)	OD (mm)	Lengths	WP (psi)	Weight (kgs/m)
20017708	3"	76.2	91.2	18.3 m	200	3.16
20017710	4"	101.6	118.8	18.3 m	200	4.65
No code	5"	127.0	147.2	18.3 m	200	7.09
No code	6"	152.0	172.6	18.3 m	200	8.55

(< = Stock size for UK)