



PLICORD® DRY CEMENT & BARYTES SOFTWALL

APPLICATION/SERVICE:

Heavy duty discharge hose designed for bulk transfer of dry cement and barytes from supply vessels to offshore platforms and drilling rigs. Identified by yellow spiral stripe for cement and orange spiral stripe for barytes.

BENEFITS:

HIGH ABRASION RESISTANCE - Thick tube of Tufsyn® is compounded for maximum abrasion resistance to give long service life.

SAFETY FACTOR - A minimum of 4:1 is maintained on all sizes from extra strong reinforcement of 4 ply textile.

DURABLE - Exclusive Goodyear™ Plioflex® cover is right for the application, to withstand the damaging effects of weathering, heat, ozone and seawater.

CONSTRUCTION:

Tube: Black Tufsyn® (static conductive)
 Reinforcement: 4 ply textile plus anti static wire
 Cover: Black Plioflex® with yellow or orange spiral stripe (wrapped finish)

BRANDING:

No branding

LENGTHS:

18.3 mtr coils (available in other lengths up to max 120 mtr)

ORDER CODE:

549274 / 549278



DIMENSIONS:

| Code | ID (ins) | ID (mm) | OD (mm) | Lengths | WP (psi) | Weight (kgs/m) |
|----------|----------|---------|---------|---------|----------|----------------|
| 20019492 | 4" | 101.6 | 123.0 | 18.3 m | 150 | 4.50 |
| 20019494 | 5" | 127.0 | 148.9 | 18.3 m | 150 | 5.72 |
| 20019496 | 6" | 152.4 | 174.0 | 18.3 m | 150 | 6.76 |

(< = Stock size for UK)