



PLICORD® DRY CEMENT HARDWALL

APPLICATION / SERVICE:

High performance suction and discharge hose for bulk transfer of dry cement, barytes and non-oily abrasive materials from supply vessels to offshore platforms and drilling rigs.

BENEFITS:

EXCEPTIONAL PERFORMANCE - Built for rugged service and long life with a 4 ply reinforcement which maintains very high safety margins over the three sizes, and a tough steel wire helix for strength and stability.

SUPERIOR WEAR RESISTANCE - A thick abrasion resistant tube compound resists wearing from cement and barytes. The Plioflex® cover gives the hose excellent protection against extreme weather conditions encountered in oilrig applications.

CONSTRUCTION:

Tube: Black Tufsyn® (static conductive)

Reinforcement: 4 ply textile and helix wire

Cover: Black Plioflex® with yellow spiral stripe (wrapped finish)

BRANDING:

'Goodyear™'

LENGTHS:

18.3 , 30.5 mtr coils (available in other lengths up to max 120 mtr)

FITTINGS:

Long tail 'hookie-type' combination nipples screwed API

ORDER CODE:

549275



DIMENSIONS:

Code	ID (ins)	ID (mm)	OD (mm)	Lengths	WP (psi)	Weight (kgs/m)
20019497	4"	101.6	121	18.3 m	150	4.59
20019498 / 20133948	5"	127	150.9	18.3 , 30.5 m	150	7.90
No code	6"	152.4	176.8		150	9.59

(< = Stock size for UK)